

SIGNATURE® 200 Standard Colors SILICONIZED POLYESTER



- Final color selection should be made from actual color chips.
- See product selection chart for gauge and color availability.
- All products available in smooth or embossed finish.
- Trim available in all colors.
- All Signature® 300 are low gloss colors.
- Polar White is a Straight Polyester.
- A 25-year limited paint warranty available for all colors upon written request except for Scarlet Red and Crimson Red, please inquire. (Outside the continental United States, please inquire.)
- Crimson Red is offered with a 3-year warranty on roof panels and 3-year on sidewall panels.
- Signature® is a registered trademark of NCI Group, Inc. KYNAR 500® is a registered trademark of Arkema, Inc. HYLAR 5000® is a registered trademark of Solvay Solexis.
- * This color is California Title 24 compliant. Availability in certain areas may be restricted or require a surcharge.
- † Except Crimson Red, which contains more than 0.06 percent lead, none of the other colors shown are lead-containing paints under 13 CFR 1303. Crimson Red should only be used for applications which comply with federal, state and local regulations for lead-containing paint.

SIGNATURE® 300 Premium Colors KYNAR 500®, HYLAR 5000®

Additional costs apply for Signature 300 finishes.



Commercial/Industrial Panel Profiles

What is Solar Reflectivity (SR)?

Solar reflectivity or reflectance is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates total reflectance. Energy Star requires a SR value of 0.25 or higher for steep slope (above 2:12) roofing and a SR value of 0.65 or higher for low slope (2:12 or less) roofing. For more information, please go to www.energystar.gov.

What is Solar Reflectivity Index (SRI)?

The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements, a roofing material must have a SRI of 29 or higher for steep slope (above 2:12) roofing and a SRI value of 78 or higher for low slope (2:12 or less) roofing. For more information, please go to www.usgbc.org.



SIGNATURE® 200 - SILICONIZED POLYESTER

	SR #	SRI #
HAWAIIAN BLUE	.32	35
CRIMSON RED	.38	42
FERN GREEN	.28	29
BURNISHED SLATE	.28	29
ASH GRAY	.48	56
SADDLE TAN	.48	56
DESERT SAND	.42	48
KOKO BROWN	.28	29
CHARCOAL GRAY	.28	29
POLAR WHITE	.58	69
RUSTIC RED	.36	40
LIGHT STONE	.50	58
GALLERY BLUE	.28	29
SOLAR WHITE	.70	85

SIGNATURE® 300 - KYNAR 500® / HYLAR 5000®

	SR #	SRI #
MEDIUM BRONZE	.33	36
SNOW WHITE	.65	79
SLATE GRAY	.37	41
ALMOND	.63	76
CLASSIC GREEN	.28	29
BROWNSTONE	.47	54
SCARLET RED	.42	47
HARBOR BLUE	.28	29
BONE WHITE	.70	85

Profile	SIGNATURE® 200								SIGNATURE® 300				
	Panel	29 GAUGE		26 GAUGE		24 GAUGE		22 GAUGE		26 GAUGE	24 GAUGE		22 GAUGE
		Galvalume Plus*	Sig 200 (Interior liner only)	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 200	Galvalume Plus*	Sig 300	Galvalume Plus*	Galvalume Plus*
 "PBR" PANEL	PBR	●	■	●		■	■	■	■	●	●	●	●
 "PBU" PANEL	PBU	●	■	●		■	■	■	■	●	●	●	●
 "PBC" PANEL	PBC	●	■	●		■	■	■	■				
 "PBD" PANEL	PBD	●	■	●		■	■	■	■				
 "PBA" PANEL	PBA	●	■	●		■	■	■	■	●	●	●	●

● Available in any quantity ■ May require minimum quantity